

Automated Large-Volume Pyrolysis

for GC-MS and GC-MS/MS

High-capacity pyrolysis with automated PAL sample handling, large-volume aluminum oxide crucibles and integrated sorbent collection for highly reproducible GC-MS and GC-MS/MS analysis.




CONCEPT

The Chromtech Pyrolysis Oven extends automated pyrolysis workflows for processing large sample amounts. Combined with large-capacity aluminum oxide crucibles and fully automated PAL RSI / PAL RTC sample handling, the system enables highly reproducible large-volume pyrolysis.

Pyrolysis products are transferred through a heated transfer line and collected on selectable sorbent materials such as Tenax®, SorbStar® or PDMS. The collected analytes are subsequently thermally desorbed, chromatographically separated and detected using Agilent GC-MS or GC-MS/MS systems.

PROCESS WORKFLOW



YOUR BENEFITS

- Large-volume pyrolysis**
Analyze significantly larger sample amounts using 600 µL and 900 µL aluminum oxide crucibles.
- Fully automated sample handling**
The PAL RSI / PAL RTC automatically transfers crucibles from the stack drawer to the quartz platform.
- Outstanding reproducibility**
Precision positioning combined with pneumatic oven locking ensures highly reproducible analytical results.
- Efficient analyte collection**
A heated transfer line enables efficient trapping on Tenax®, SorbStar® or PDMS sorbent materials.
- Optimized for Agilent GC-MS and GC-MS/MS systems**
Designed for seamless integration with Agilent Single Quadrupole and Triple Quadrupole platforms.

TECHNICAL SPECIFICATIONS

Temperature range	Up to 1000 °C
Heating rate	Up to 50 °C/min
Crucible material	Aluminum oxide
Crucible volume	600 µL / 900 µL
Stack capacity	Up to 80 crucibles
Transfer line	Heated, up to 400 °C
Sorbent materials	Tenax®, SorbStar®, PDMS
Sample handling	PAL RSI / PAL RTC
Detection	Optimized for Agilent GC-MS / GC-MS/MS
Dimensions (W x D)	Approx. 1300 x 300 mm (extended)



PYROLYSIS OVEN

Up to 1000 °C for efficient and reproducible large-volume pyrolysis.



AUTOMATED STACK DRAWER

High-capacity stack for up to 80 crucibles ensures maximum sample throughput.



PAL HANDLING INTERFACE

Precise and reliable sample transfer from the stack to the pyrolysis platform.



CHROMTECH GmbH
Carl-Zeiss-Straße 20
65520 Bad Camberg
Germany

+49 6434 20768-0
info@chromtech.de
www.chromtech.de